

ORLEN OIL MAX EXPERT A5/B5 0W-30

General characteristics:

Synthetic, modern, all-season engine oil for the latest petrol and diesel engines. The precise formulation using the latest technology and refining additives guarantees maximum output of the power unit together with the comprehensive protection of the engine. Meets one of the latest specifications by Volvo.

Guarantees:

- fuel economy,
- extends the life of the engine,
- · maintains engine cleanliness

Application:

Oil ORLEN OIL MAX EXPERT A5/B5 0W-30 is designed for the application in both gasoline and diesel engines. Meeting the requirements of ACEA quality classification, it guarantees a high level of protection, even under heavy loads and in tough working conditions. It works perfectly both in the city traffic conditions and on highways. The oil is compatible with exhaust treatment devices in Volvo engines which require the Volvo approval 9520037. It can be used in other vehicles which meet Euro 6 emission standards, for which the manufacturer recommends oil viscosity class and quality specified below.

Viscosity class:

SAE: 0W-30

Quality class:

API: SL ACEA A5/B5

Standards, approvals, specifications:

Volvo 95200377

Physical and chemical parameters:

| Parameters | Units of measurement | Typical values |
|------------------------------|----------------------|----------------|
| SAE viscosity class | - | 0W-30 |
| kinematic viscosity at 100°C | mm²/s | 10.3 |
| viscosity index | - | 160 |
| pour point | °C | -40 |
| flash point | °C | 230 |
| CCS at -35°C | mPa*s | 6100 |
| Total Base Number TBN | mg KOH/g | 8 |

Note: The above values of physical and chemical parameters are typical values. The actual values are indicated in the quality certificates attached to each product batch.