



ORLEN OIL AGRO LS 80W-90

General features

Mineral high quality transmission oil for all-year use in transmission of tractors, harvesters and other agricultural machinery. Recommended in particular for Limited Slip differentials.

Guarantee:

- high load bearing ability;
- excellent lubricating and anti-wear properties;
- outstanding anti-foaming performance;
- excellent thermal and oxidation stability.

Application

ORLEN OIL Agro LS 80W-90 multigrade transmission oil is recommended for lubrication of manual transmissions of various agricultural equipment operated in severe conditions. It is recommended for use in tractors, combines and other agricultural machinery with this viscosity and quality grade specified by manufacturers.

It is recommended particularly for use in heavy-duty vehicles, agricultural equipment and other machinery with for Limited Slip differentials.

Quality class

API: GL-5

Viscosity grad

SAE: 80W-90

Standards, approvals, specifications

ZF TE-ML 05C, 21C (ZF011924)

Meets requirements:

DTFR 12B100,
MIL-L-2105D,
MAN 342 M-1,
Voith 3.325-339,
Volvo 97310,
Volvo 97316,
Renault
ZF TE-ML 07A, 08, 16B, 17B, 19B, 21A,
DAF

Physical and chemical properties

Parameters	Unit	Typical values
SAE viscosity grade	-	80W-90
Kinematic viscosity at 100 °C	mm ² /s	14,8
viscosity index	-	98
Flow temperature	°C	-30
Flash point	°C	230
Note: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each production batch.		

v1 / 2024-02-27